

# SECTEC

Always keep an eye on your safety

[www.sectec.com.cn](http://www.sectec.com.cn)



## About SECTEC >>

Shenzhen Sectec Co., Ltd is a R&D-oriented manufacturer and mainstream provider for advanced security and surveillance system products in China. Founded in Year 2001,

Sectec has developed rapidly by its excellent performance in CCTV field. Sectec products range from CCTV Camera, IP Camera, network digital video Recorder, DVR, wired camera, wireless camera, USB DVR, NVR, HVR, video capture card, CCTV accessories and so on, totally are hundreds of models.

Sectec provides OEM and ODM service for your market requirement with our quality assurance.

Shenzhen Sectec series products have been certified by CE, FCC, won ISO 9001:2000 approval.

Principle:

Creates with the technology performance;

Creates with the service future

Win the customer with the quantity.

Welcome send inquiry to our company,

we will be glad to establish friendly business relationships with your esteemed company!

2013.8

SECTEC-----YOUR RELIABLE SECURITY SUPPLIER



[www.sectec.com.cn](http://www.sectec.com.cn)

**Contents:**

- 1 HD SDI camera
- 2 MP IP camera
- 3 CCTV analog camera
- 4 DVR
- 5 NVR
- 6 HVR
- 7 Kits
- 8 ACCESSORIES



## ST-MP559-960P

1) Dual stream encoding (H.264/MJPEG)2)

1/3-inch Aptina 1.3 Megapixel Low Lux AR0130 CMOS  
(0.01Lux)

960P 1280\*960

Support Multi-Screen software and CMS

Support Protocol: TCP, UDP, IP, HTTP, SMTP, DHCP, DNS, ARP, ICMP  
POP3, NTP, IPsec, UPnP, RTP,

RTCP Can be placed under the eaves

20m IR with 30pcs leds, 3.6mm lens

[www.sectec.com.cn](http://www.sectec.com.cn)

HD  
960P  
IP



**ST-SDI305T**

**1/3" Sony 2M pixel CMOS/1080P30FPS,  
Full HD Mega Pixel(1080P)**

**2.8-12mm 2M Pixels ICR+DC Lens  
IR LED: 5X42PCS 40M**

**WDR + IR-CUT**

**Motion Detection,  
Digital Zoom**







## ST-SDI292T

1/3" Sony 2M pixel CMOS

30fps@ 1080P,/ 60fps@720P Full HD Mega Pixel

## ST-SDI292E

1/2.8" Panasonic 2.2M pixel CMOS

30fps@ 1080P,/60fps@ 720P Full HD Mega Pixel

- IR LED: 5X30PCS,IR LED Range: 30M
- Lens:2M Pixels ICR+DC Lens 2.8-12mm
- Support WDR,3D-DNR,IR-CUT
- OSD cable control,
- Motion Detection,
- Digital Zoom
- SDI and video double signal Output
- Material: metal



## ST-SDI291T

1/3" Sony 2M pixel CMOS

30fps@ 1080P,/ 60fps@720P Full HD Mega Pixel

## ST-SDI291E

1/2.8" Panasonic 2.2M pixel CMOS

30fps@ 1080P,/60fps@ 720P Full HD Mega Pixel

- IR LED: 5X30PCS,IR LED Range: 30M
- Lens:2M Pixels ICR+DC Lens 2.8-12mm
- Support WDR,3D-DNR,IR-CUT
- OSD cable control,
- Motion Detection,
- Digital Zoom
- SDI and video double signal Output
- Material: metal

**ST-SDI159T**

1/3" Sony 2M pixel CMOS

30fps@ 1080P,/ 60fps@720P Full HD Mega Pixel

**ST-SDI159E**

1/2.8" Panasonic 2.2M pixel CMOS

30fps@ 1080P,/60fps@ 720P Full HD Mega Pixel

- IR LED: 5X21PCS,IR LED Range: 20M
- Lens:2M Pixels ICR+DC Lens 2.8-12mm
- Support WDR,3D-DNR,IR-CUT
- OSD cable control,
- Motion Detection,
- Digital Zoom
- SDI and video double signal Output
- Material: metal

**ST-SDI62T**

1/3" Sony 2M pixel CMOS

30fps@ 1080P,/ 60fps@720P Full HD Mega Pixel

**ST-SDI62E**

1/2.8" Panasonic 2.2M pixel CMOS

30fps@ 1080P,/60fps@ 720P Full HD Mega Pixel

- IR LED: 5X21PCS,IR LED Range: 20M
- Lens:2M Pixels ICR+DC Lens 2.8-12mm
- Support WDR,3D-DNR,IR-CUT
- OSD cable control,
- Motion Detection,
- Digital Zoom
- SDI and video double signal Output
- Material: metal





## ST-SDI304T

1/3" Sony 2M pixel CMOS

30fps@ 1080P,/ 60fps@720P Full HD Mega Pixel

## ST-SDI304E

1/2.8" Panasonic 2.2M pixel CMOS

30fps@ 1080P,/60fps@ 720P Full HD Mega Pixel

- IR LED: 5X42PCS,IR LED Range: 40-45M
- Lens:2M Pixels ICR+DC Lens 2.8-12mm
- Support WDR,3D-DNR,IR-CUT
- OSD cable control,
- Motion Detection,
- Digital Zoom
- SDI and video double signal Output
- Material: metal,waterproof



## ST-SDI301T

1/3" Sony 2M pixel CMOS

30fps@ 1080P,/ 60fps@720P Full HD Mega Pixel

## ST-SDI301E

1/2.8" Panasonic 2.2M pixel CMOS

30fps@ 1080P,/60fps@ 720P Full HD Mega Pixel

- IR LED: 5X42PCS,IR LED Range: 40-45M
- Lens:2M Pixels ICR+DC Lens 2.8-12mm
- Support WDR,3D-DNR,IR-CUT
- OSD cable control,
- Motion Detection,
- Digital Zoom
- SDI and video double signal Output
- Material: metal,waterproof

**ST-SDI383T**

1/3" Sony 2M pixel CMOS

30fps@ 1080P,/ 60fps@720P Full HD Mega Pixel

**ST-SDI383E**

1/2.8" Panasonic 2.2M pixel CMOS

30fps@ 1080P,/60fps@ 720P Full HD Mega Pixel

- IR LED: 5X42PCS,IR LED Range: 40-45M
- Lens:2M Pixels ICR+DC Lens 2.8-12mm
- Support WDR,3D-DNR,IR-CUT
- OSD cable control,
- Motion Detection,
- Digital Zoom
- SDI and video double signal Output
- Material: metal,waterproof

**ST-SDI316T**

1/3" Sony 2M pixel CMOS

30fps@ 1080P,/ 60fps@720P Full HD Mega Pixel

**ST-SDI316E**

1/2.8" Panasonic 2.2M pixel CMOS

30fps@ 1080P,/60fps@ 720P Full HD Mega Pixel

- IR LED: 5X54PCS,IR LED Range: 55M
- Lens:2M Pixels ICR+DC Lens 2.8-12mm
- Support WDR,3D-DNR,IR-CUT
- OSD cable control,
- Motion Detection,
- Digital Zoom
- SDI and video double signal Output
- Material: metal,waterproof

ONVIF 2.0



## ST-IP934-1M

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

## ST-IP934-1.3M

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

## ST-IP934-2M

- Image sensor : HS3516C+1/2.5" Aptina 9P006 Sensor
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X30pcs,IR Range:35M
- Lens :4/6/8mm fixed lens
- Build in IR CUT ●Color:White Gray

ONVIF 2.0



## ST-IP709-1M

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

## ST-IP709-1.3M

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

## ST-IP709-2M

- Image sensor : HS3516C+1/2.7" Sony CMOS IXM 122
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X42pcs,IR Range:40-45M
- Lens :2.8-12mm varifocal lens
- Build in IR CUT ●Color:White Gray

ONVIF 2.0

**ST-IP935-1M**

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

**ST-IP935-1.3M**

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

**ST-IP935-2M**

- Image sensor : HHS3516C+1/2.5" Aptina 9P006 Sensor
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X36pcs,IR Range:35M
- Lens :2.8-12mm varifocal lens
- Build in IR CUT ●Color:White Gray

ONVIF 2.0

**ST-WIP935-1M**

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

**ST-WIP935-1.3M**

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X36pcs,IR Range:35M
- Lens :2.8-12mm varifocal lens
- Build in IR CUT ●Color:White Gray



ONVIF 2.0



## ST-IP7024-1M

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

## ST-IP7024-1.3M

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

## ST-IP7024-2M

- Image sensor : HS3516C+1/2.7" Sony CMOS IXM 122
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X36pcs,IR Range:35M
- Lens :2.8-12mm varifocal lens
- Build in IR CUT ●Color:White Gray

ONVIF 2.0



## ST-IP121-1M

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

## ST-IP121-1.3M

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

## ST-IP121-2M

- Image sensor : HS3516C+1/2.7" Sony CMOS IXM 122
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X42pcs,IR Range:40-45M
- Lens :2.8-12mm varifocal lens
- Build in IR CUT ●Color:White Gray



# Onvif Mega Pixel IP camera

ONVIF 2.0



## ST-IP7030-1M

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

## ST-IP7030-1.3M

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

## ST-IP7030-2M

- Image sensor : HS3516C+1/2.7" Sony CMOS IXM 122
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X42pcs,IR Range:45M
- Lens :2.8-12mm varifocal lens
- Build in IR CUT ● Color:White Gray

ONVIF 2.0



## ST-NVR KIT

4pcs\*720P IP Camera +1pc \* 4CH P2PNVR

- Camera 1MP:1280\*720
- Dual stream encoding
- H.264 compression mode
- 1/4"-inch OV9712 CMOS, 4mm fixed lens
- Night vision :20m(36pcs leds)
- NVR Hi 3520A
- Support 4CH 720P/2CH 1080P realtime viewing and recording
- Support 4CH 720P/1CH 1080P playback
- Support 1CH BNC/VGA/HDMI output

ONVIF 2.0



## ST-IP623-1M

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

## ST-IP623-1.3M

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

## ST-IP623-2M

- Image sensor : HS3516C+1/2.7" Sony CMOS IXM 122
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X21pcs,IR Range:25M
- Lens :2.8-12mm varifocal lens
- Build in IR CUT ●Color:White Gray

ONVIF 2.0



## ST-IP559-1M

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

## ST-IP559-1.3M

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

## ST-IP559-2M

- Image sensor : HS3516C+1/2.7" Sony CMOS IXM 122
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X30pcs,IR Range:30M
- Lens :3.6mm fixed lens
- Build in IR CUT ●Color:White Gray

ONVIF 2.0

**ST-IP559V-1M**

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

**ST-IP559V-1.3M**

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

**ST-IP559V-2M**

- Image sensor : HS3516C+1/2.7" Sony CMOS IXM 122
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X30pcs,IR Range:30M
- Lens :2.8-12mm varifocal lens
- Build in IR CUT ●Color:White Gray

ONVIF 2.0

**ST-IP716-1M**

- Image sensor : HS3518+1/4" OV 1M CMOS
- 30fps@ 720P ,Max:1280\*720
- Min. Illumination :0.1Lux @(F1.2,AGC ON),

**ST-IP716-1.3M**

- Image sensor :HS3518+1/3" Aptina super low Lux
- 30fps@ 960P, Max:1280\*960
- Min. Illumination :0.01Lux @(F1.2,AGC ON),

**ST-IP716-2M**

- Image sensor : HS3516C+1/2.7" Sony CMOS IXM 122
- 30FPS 1080P, Max:1920\*1080
- Min. Illumination :0.001Lux @(F1.2,AGC ON)

- Compression :H.264 High Profile
- Support Multi-Screen software and CMS
- 0 LUX with IR
- IR LED: 5X30pcs,IR Range:30M
- Lens :2.8-12mm varifocal lens
- Build in IR CUT ●Color:White Gray

## ST-IPC9907



- \*It is a multifunctional product including video call function, remote monitor function, local recording function and wireless alarm function, which can satisfies your different needs.
- \*It introduces advanced Cloud link P2P network transmission technology, so that it can switch bitrates intelligently and adapt to any network environment.
- \*Built-in 3C smart card, it is so easy to realize remote monitor and video call.
- \*It introduces 3Dvoice sound engine technology, which can thoroughly improve the quality of network sound call.
- \*H.264 Main Profile compression, which can make clearer and smoother image.
- \*It has intuitive and user-friendly operation interface, you can start it without training.
- \*It can support these two APP programs---IOS and Android, through APP program, you can care family anytime and anywhere.

\*Video phone: High Performance Embedded Microprocessor Hi3512, Embedded Linux OS



\*Recorder:



\*Alarm:



\*IP camera:





# 12 Pixim camera

## ST-PIX100



- PIXIM 1/3 SEAWOLF Solution
  - 690HTVL-E
  - WDR:120dB (max)
  - With OSD
- Varifocal lens 2.8-10mm  
IR LED:42uX2PCS IR LED

## ST-PIX80



- PIXIM 1/3 SEAWOLF Solution
  - 690HTVL-E
  - WDR:120dB (max)
  - With OSD
- Varifocal lens 4-9mm  
IR LED:42uX2PCS IR LED

## ST-37



- PIXIM 1/3 SEAWOLF Solution
  - 690HTVL-E
  - WDR:120dB (max), Sens-Up: 1-32times
  - Min 0lux (IR on), 3D motion adeptive
  - With OSD
- Varifocal lens 2.8-12mm  
IR LED:30pcs IR LED, 30m IR

## ST-P600



- PIXIM 1/3 SEAWOLF Solution
  - 690HTVL-E
  - WDR:120dB (max), Sens-Up: 1-32times
  - Min 0lux (IR on), 3D motion adeptive
  - With OSD
- Power Input: 12V/ 24V

## ST-0100



- PIXIM 1/3 SEAWOLF Solution
  - 690HTVL-E
  - WDR:120dB (max), Sens-Up: 1-32times
  - Min 0lux (IR on), 3D motion adeptive
  - With OSD
- Lens: 3.7mm pinhole lens  
Power Input: 12V/ 24V

## ST-0515



- PIXIM 1/3 SEAWOLF Solution
  - 690HTVL-E
  - WDR:120dB (max)
  - With OSD
- Varifocal lens 4-9mm  
IR Distance: 50M



## ST-C760K/N/C/A, ST-R758A/R760K/E/P



- 600TVL/900TVL/1000TVL/1200TVL CMOS CHIP
- 450TVL/600TVL/700TVL/960TVL SONY CCD
- 2.8-12mm focus lens
- IR LEDs:36pcs, 35m Smart IR
- WDR, OSD, IP65,DC12V
- Metal housing
- Dimension:120x 99(H)mm, W.t:0.85KG

## ST-C858K/N/C, ST-R758/R760T/H



- 600TVL/900TVL/1000TVL CMOS CHIP
- 450TVL/500TVL/600TVL/700TVL SONY CCD
- 3.6mm fixed lens
- IR LEDs:24pcs, 25m Smart IR
- WDR, OSD, IP65,DC12V
- Plastic housing
- Dimension:94x 69(H)mm, W.t:0.45KG

## ST-BB65/BB65K/T/E



- 450TVL/560TVL/600TVL/700TVL
- 1/3" Sony SUPER HAD CCD
- 4-9mm focus lens(2.8-11mm optional)
- IR LEDs:21pcs, 20m Smart IR
- WDR, OSD, IP65,DC12V
- Metal housing
- Dimension:120x 99(H)mm, W.t:0.85KG

## ST-R761/R761H/T/E/S/P



- 450TVL/500TVL/600TVL/700TVL/900TVL/960TVL
- 1/3" Sony SUPER HAD CCD
- 2.8-12mm focus lens
- IR LEDs:2pcs Dot-matrix, 50m Smart IR
- WDR, OSD, IP65,DC12V
- Metal housing
- Dimension:100x 119(H)mm, W.t:0.62KG

## ST-R716B/K/T/E/S/P



- 450TVL/500TVL/600TVL/700TVL/900TVL/960TVL
- 1/3" Sony SUPER HAD CCD
- 2.8-12mm varifocal lens
- IR LED: 30pcs, 30m Smart IR
- WDR,OSD, IP65,DC12V
- Bulit in bracket,Metal housing
- Dimention: 98(H)\*148(D), W.t:0.95KG

## ST-R799/H/K/E/P



- 450TVL/500TVL/600TVL/700TVL/960TVL
- 1/3" Sony SUPER HAD CCD
- 4-9mm varifocal lens(2.8-12mm optional)
- IR LED: 36pcs, 35m Smart IR
- WDR,OSD, IP65,DC12V
- Deep Base,Metal housing
- Dimension:120 x 99(H) mm, W.t:0.85KG

# 14 Analog camera

## ST-C7015K/N/C, ST-7015/7015H/T/E



- 600TVL/900TVL/1000TVL CMOS COLOR CHIP
- 450TVL/500TVL/600TVL/700TVL SONY CCD
- 6mm fixed lens(6mm optional)
- IR LEDs:24pcs, 25m Smart IR
- WDR,OSD, IP66,DC12V
- Bulit in bracket,Metal housing
- Dimension:86x60x55mm, W.t:0.4kg

## ST-C772K/N/C/A, ST-R772/9/1E/1P



- 600TVL/900TVL/1000TVL/1200TVL CMOS CHIP
- 450TVL/600TVL/700TVL/960TVL SONY CCD
- 2.8-12mm focus lens
- IR LEDs:42pcs, 45m Smart IR
- WDR, OSD, IP66,DC12V
- Bulit in bracket, Metal housing
- Dimension:200\*171\*83mm, W.t:1.5kg

## ST-7125



- 600TVL,1/3"Sony SUPER HAD CCD,DWDR
- 0.00045Lux/F1.2, Star light sensitivity,
- Auto sense up,Max 32x sense up
- Black front glasses to avoid ligh flickness
- 2.8-12mm varifocal lens
- IP66,DC12V
- Bulit in bracket,Metal housing
- Dimension: 141\*83\*171mm, W.t: 1.2kg

## ST-R1018/T/E/P



- 450TVL/600TVL/700TVL/960TVL
- 1/3" Sony SUPER HAD CCD
- 6mm CS Lens/F1.4
- IR LED: 1 PCS Array IR led, 35m Smart IR
- WDR,OSD, IP66,DC12V
- Bulit in bracket,Metal housing
- Dimension:174x75x124mm, W.t : 0.9KG

## ST-9910/9910T/E/P



- 450TVL/600TVL/700TVL/960TVL
- 1/3" Sony SUPER HAD CCD
- 2.8-12mm fixed lens
- IR LEDs:41pcs, 40m Smart IR
- WDR, OSD, IP66,DC12V
- Built in Bracket, waterproof
- Dimension:280x 102(H)mm, W.t:2KG

## ST-ST-FD406/408/409/418



- 450TVL/600TVL/700TVL/960TVL
- 1/3" Sony SUPER HAD CCD
- 2.8-12mm fixed lens
- IR LEDs:2pcs Dot-matrix, 50m,0.00045Lux/F1.2
- WDR, OSD, IP66,DC12V
- Built in Bracket, waterproof
- Dimension:280x 102(H)mm, W.t:2KG



## ST-720EB



- 700TVL, Effio, 1/3" Sony SUPER HAD CCD
- Lens: 3.6/6mm board lens
- IR LED: 5 \* 24pcs, 20m IR night vision
- Dual Color: White
- Dimension of package: 590\*360\*200mm
- 30pcs/ctn Weight: 0.5kg

## ST-C7025N, ST-7024/H/7025T/7026E



- 900TVL 960H CMOS New solution
- 450TVL/500TVL/600TVL/700TVL Sony SUPER
- 4-9mm focus (2.8-12mm optional)
- IR LEDs: 36pcs, 35-40m
- WDR, OSD, IP66, DC12V
- Metal housing

## ST-7019EB



- 700TVL, Effio, 1/3" Sony SUPER HAD CCD
- Lens: 2.8-12mm 2MP varyfocus lens
- IR LED: 5 \* 42pcs, 40m IR night vision
- OSD menu, 960H, WDR
- Color: White/grey

## ST-7016EB



- 700TVL, Effio, 1/3" Sony SUPER HAD CCD
- Lens: 3.6/6mm board lens
- IR LED: 5 \* 24pcs, 20m IR night vision
- Dual Color: White, black optional
- Dimension of package: 590\*360\*200mm
- 30pcs/ctn Weight: 0.5kg

## ST-FD805B



- 450TVL/500TVL/600TVL/700TVL
- 850TVL/960TVL Sony SUPER CCD
- 2.8-12mm focus lens
- IR LEDs: 72pcs, 60m
- WDR, OSD, IP66, DC12V
- Bulit in bracket, waterproof
- Dimension: 295x120x103mm, W.t: 1.8kg

## ST-7018K/H/Z/N, ST-R7018/R7018T/E



- 600TVL/750TVL/850TVL/900TVL CMOS CHIP
- 450TVL/600TVL/700TVL/ Sony SUPER CCD
- 3.6mm fixed lens
- IR LEDs: 24pcs, 25m
- WDR, OSD, IP66, DC12V
- Bulit in bracket, waterproof
- Dimension: 228x97x82mm, W.t: 0.5kg

## ST-RB720H/K/E/S/P



500TVL/600TVL/700TVL/900TVL/960TVL  
 1/3" Sony SUPER HAD CCD  
 -2.8-12mm focus lens  
 -IR LEDs:36pcs big leds, 50m Smart IR  
 -WDR,OSD, IP66,DC12V  
 -Bulit in bracket, waterproof  
 -Dimension:255\*152\*144mm, W.t:0.9kg

## ST-DM718/DM718K/E/S/P



450TVL/600TVL/700TVL/900TVL/960TVL  
 1/3" Sony SUPER HAD CCD  
 -2.8-12mm focus lens(5-50mm,9-22mm optional)  
 -2pcs Dot IR with 7 pcs fish eye led, 50m  
 -WDR,OSD, IP66,DC12V  
 -Bulit in bracket, waterproof  
 -Dimension:255\*152\*144mm, W.t:1kg

## ST-WD705/708/709/709P



450TVL/600TVL/700TVL/960TVL  
 1/3" Sony SUPER HAD CCD  
 -2.8-12mm 2M Pixel lens  
 -IR LEDs: 42pcs, 50m Smart IR  
 -WDR,OSD, IP66,DC12V  
 -Bulit in bracket, waterproof  
 -Dimension:255\*152\*144mm, W.t:1kg

## ST-DM816/816K/816E/816S/816P



450TVL/600TVL/700TVL/900TVL/960TVL  
 1/3" Sony SUPER HAD CCD  
 -2.8-12mm focus lens(5-50mm,9-22mm optional)  
 -3pcs Dot IR with 14 pcs fish eye led, 50m  
 -WDR,OSD, IP66,DC12V  
 -Bulit in bracket, waterproof  
 -Dimension:255\*152\*144mm, W.t:2kg

## ST-DM601F/603F/606F/608F



450TVL/600TVL/700TVL/960TVL  
 1/3" Sony SUPER HAD CCD  
 -2.8-12mm 2M Pixel lens  
 -IR LEDs: 2pcs Dot-matrix, 50m Smart IR  
 -WDR,OSD, IP66,DC12V  
 -Bulit in bracket, waterproof  
 -Dimension:209\*90mm, W.t:2kg

## ST-WD701/703/706/701E/701P



450TVL/560TVL/600TVL/700TVL/960TVL  
 1/3" Sony SUPER HAD CCD  
 -2.8-12mm focus lens  
 -IR LEDs:42pcs, 50m  
 -WDR,OSD, IP66,DC12V  
 -Bulit in bracket, waterproof, Dual glass  
 -Dimension:255\*152\*144mm, W.t:2kg

## ST-C7416M/K/V, ST-R7416/7416K/H/E



- 520TVL/600TVL/700TVL CMOS CHIP
- 450TVL/500TVL/600TVL/700TVL/ Sony SUPER CCD
- 3.6mm fixed lens
- IR LEDs: 23pcs, 20-25m
- WDR, OSD, IP66, DC12V
- Bulit in bracket, waterproof
- Dimension: 104x65x119mm , W.t: 0.5kg

## ST-R624/624T/624H/624E/624P



- 450TVL/600TVL/650TVL/700TVL/960TVL
- 1/3" Sony SUPER HAD CCD
- 4-9mm focus (2.8-12mm, auto iris VF lens optional)
- IR LEDs: 36pcs, 35-40m
- WDR, OSD, IP66, DC12V
- Metal housing

## ST-WD213/214



- 600TVL, 1/3" Sony SUPER HAD CCD
- Mini dome camera standard 360° wide
- Angle camera hemisphere
- Lens: 1.2MM (1.75mm optional)
- Day & night Auto/Color/BW

## ST-R610L/610C/610H/610E/610P



- 450TVL/500TVL/600TVL/700TVL/960TVL
- 1/3" Sony SUPER HAD CCD
- 4-9mm focus (2.8-12mm, optional)
- IR LEDs: 36pcs, 35-40m
- Vandalproof IR Dome
- WDR, OSD, IP66, DC12V
- Dimention: 139mm\*97(H), W.t: 0.85KG

## ST-ALS05



- Analog PTZ camera:
- \*1/4" CCD , 450TVL, 27x zoom camera
- \*Auto/manual,
- \*Take high-performance DSP to realise complete digital and ultra-high speed focus function
- \*4 groups, 16 presets join tour
- \*The preset residence time can be set
- 150 m infrared lamp array

## ST-37



- 600TVL, PIXIM 1/3 SEAWOLF Solution, 0lux
- 2.8-12MM Auto Iris Lens
- WDR: 120dB (max)
- OSD
- IR-CUT
- Power Input : 12VDC / 24V AC



## ST-HD-i DVR6009DA-PEL

**HD-SDI**  
**FULL HD**  
 1920x1080


- \*Video-in: 1 HI-SDI+8 BNC
- out: 1 HDMI+1 VGA OUT+ 2 BNC
- \*Audio: 4ch in+1ch out
- \*Alarm: 8ch in+1ch out
- \*Encoding: 1ch HD-SDI 1080P @25/30 fps
- +8ch D1@200/240 fps.
- \*Cloud technology (www.xmeye.net)
- \*Intelligent Analysis.(PEA,OSC,CPC,AVD)
- \*DVR HVR NVR 3 in 1.
- \*2 SATA up to 6 TB , RS485,RS232,USB2.0
- \*Support 3G, WIFI. CPU: 1 \* HI3521

## ST-HD-iDVR6032F-S



- \*Video: 8ch D1+24ch CIF in, 4ch out
- \*Audio: 16ch in+1ch out
- \*Alarm: 16ch in+4ch out
- \*Encoding: 8ch D1 @200/240 fps
- +24ch CIF @100/120fps
- \*Cloud technology (www.xmeye.net)
- \*Intelligent Analysis.(PEA,OSC,CPC,AVD)
- \*DVR HVR NVR 3 in 1.
- \*4 SATA up to 12 TB , RS485,RS232,USB2.0
- \*Support 3G, WIFI. CPU: 1 \* HI3521

## ST-DVR8016



- Economic H.264 network DVR
- \*Video: 16ch CIF in, 1ch out
- \*Audio: 4ch in+1ch out
- \*Alarm: 4ch in+1ch out
- \*Encoding: 16ch CIF @100/120fps
- \*Cloud technology (www.xmeye.net)
- \*Intelligent Analysis.(PEA,OSC,CPC,AVD)
- \*2 SATA, RS485,RS232,USB2.0
- \*Support 3G, WIFI. CPU: 1 \* HI3531
- Optional function:HDMI, OUT 3G

## ST-HVR6204A



- Economic H.264 network HVR
- \*Video: 4ch 960H in, 1ch out
- \*Audio: 4ch in+1ch out
- \*Alarm: 4ch in+1ch out
- \*Cloud technology (www.xmeye.net)
- DVR mode:4CH\*960H/4CH\*D1
- HVR mode:2 \*D1+(1\*1080P+1\*720P)
- NVR mode:8\*960H/ 4\*720P/ 2\*1080P/ 1\*720P+
- 7\*D1/ 1\*1080P+1\*720P+2\*D1
- Support 3G & Wifi & HDMI output, CPU:3520A

## ST-NVR6004/6008



- \*4/8 ch 1080P IP input
- \*4/8 Channel simultaneous realtime playback
- \*Up to 4/8ch 1080P cameras realtime live view
- 1 SATA HDDs support,
- USB 2.0,
- smart phone monitoring(windows mobile),
- Dual-core

## ST-NVR6016/6024



- \*16\*1080P @30fps/16\*720P/24\*D1
- 24\*1080P @30fps/32\*720P/32\*D1
- \*Support 3G/WIFI
- \*Spot output, 1/4/9 Screen preview
- \*10M/100M/1000M network
- Support Maximum 4x 3T SATA HDD
- VGA+HDMI+PTZ+IR controller+Mouse
- +Power supply Adapter

## ST-KITC858M/K/855/858/860K/860B



520TVL/600TVL CMOS CHIP  
 450TVL/480TVL/600TVL/700TVL/ Sony SUPER CCD  
 1pc\*4ch D1 H.264 network DVR  
 Cloud tech, Haisi chip, 4ch Video in, 1ch audio  
 4\*Color CCD IR Dome cameras  
 4\*10m video cable  
 1\*5way cable  
 1\*4A, 12V  
 1\* color package box

## ST-KITC7085M/K/7085/7085S/T/EB



520TVL/600TVL CMOS CHIP  
 450TVL/480TVL/600TVL/700TVL/ Sony SUPER  
 1pc\*4ch D1 H.264 network DVR  
 Cloud tech, Haisi chip, 4ch Video in, 1ch audio  
 4\*Color CCD cameras (2 waterproof + 2 IR Dome)  
 4\*10m video cable  
 1\*5way cable  
 1\*4A, 12V  
 1\* color package box

## ST-KITC7015M/K/7015/7015S/K/EB



520TVL/600TVL CMOS CHIP  
 450TVL/480TVL/600TVL/700TVL/ Sony SUPER  
 1pc\*4ch D1 H.264 network DVR  
 Cloud tech, Haisi chip, 4ch Video in, 1ch audio  
 4\*Color CCD waterproof cameras  
 4\*10m video cable  
 1\*5way cable  
 1\*4A, 12V  
 1\* color package box

## ST-KITC758M/K/R755/R758/R760T/BS



520TVL/600TVL CMOS CHIP  
 450TVL/480TVL/600TVL/700TVL/ Sony SUPER  
 1pc\*4ch D1 H.264 network DVR  
 Cloud tech, Haisi chip, 4ch Video in, 1ch audio  
 4\*Color CCD IR Dome cameras  
 4\*10m video cable  
 1\*5way cable  
 1\*4A, 12V  
 1\* color package box

## ST-C101M/C101K/C101Z



520TVL/600TVL/700TVL CMOS CHIP  
 1pc\*4ch D1 H.264 network DVR  
 Cloud tech, Haisi chip, 4ch Video in, 1ch audio  
 4\*Color CCD waterproof cameras  
 4\*10m video cable  
 1\*5way cable  
 1\*4A, 12V  
 1\* color package box

## ST-KITC760K/R758A/R760K/R760B



600TVL CMOS  
 450TVL/600TVL/700TVL SUPER SONY CCD  
 1pc\*4ch D1 H.264 network DVR  
 Cloud tech, Haisi chip, 4ch Video in, 1ch audio  
 4\*Color CCD waterproof cameras  
 4\*10m video cable  
 1\*5way cable  
 1\*4A, 12V  
 1\* color package box



## STest-896



3.5" TFT-LCD,  
 LCD Brightness/Contrast/Color S22aturation  
 NTSC/PAL auto display, Video Level testing  
 NTSC/PAL colorbar generator  
 PTZ controller, UTP cable tester  
 PTZ data analyst, PTZ address scanning  
 DC12V 1A power output for camera  
 Audio testing, Optical power meter  
 Battery support 12 hours working time

## ST-M035LCD



## 3.5" CCTV TESTER

\*Able to use in any place any time  
 \*Rechargeable battery  
 \*Hand hold design for professional,  
 easy to operation  
 \*Support DC power for camera

## ST-216



1 Channel passive video transceiver via UTP cable  
 Video/Color 400 Meters/B/W 600 Meters

## ST-VB800



8ch passive video balun w  
 terminal block and cable BNC-M -Metal case  
 Video/Color 500 Meters/B/W 800 Meters  
 Extended Male BNC and RJ 45

## ST-P100/200



1A, 12V, 100pcs/CTN, 16KG/CTN  
 2A, 12V, 100pcs/CTN, 17KG/CTN

## ST-P300/400/500/600/800



3A, 12V, 100pcs/CTN, 21KG/CTN  
 4A, 12V, 100pcs/CTN, 27KG/CTN  
 5A, 12V, 100pcs/CTN, 27KG/CTN  
 6A, 12V, 100pcs/CTN, 27KG/CTN  
 8A, 12V, 100pcs/CTN, 30KG/CTN

## ST-B1230-6CH

12V DC 3 Amp 6CH UPS



Input: AC100-240V; Output: DC12V 10A  
 9outputs; fuse type: glass(Default) or PTC

## ST-P122BS



Waterproof power box with bracket  
 12V, 2A ; L206\*W126\*H79

## ST-DC08



DC 2.1/5.5 Adaptor, DC(female) to 2PIN connector

## ST-DC05



DC 2.1/5.5 Adaptor, DC(male) to 2PIN connector

ST-12B



BNC male , with screw inside

ST-01B



RG59 connector

ST-RG59



RG59 connector

ST-6M



RG6 connector

ST-DC02



DC 2.1/5.5, Female type

ST-DC09



DC Plug female to female

ST-DC06



DC 2.1/5.5 Adaptor, DC to 2PIN connector

ST-DC04



DC (female) to 2PIN connector (pluggable)

ST-09N



BNC connector

ST-06B



BNC-F, work with ST-65F together

ST-C04



1 to 4way cable splitter

ST-VC20



20M BNC Power and Video Coaxial Cable

ST-5040



Aluminum, waterproof camera bracket

ST-5051C



4.5inch metal dome camera, Metal bracket

ST503DVP-3/12V

Monitoring, video+485 control+12V power,  
three-in-one protection

SSV02812GNB

2.8 12mm 1/3" CS F1.4 101° 28°  
DC manual zoom

www. **SECTEC** .com.cn



SECTEC CO.,LIMITED